JEAN MÜLLER
THE NAME FOR SAFETY

Type designation: MooogL100

Article number: N5014305

Images



(Illustration similar)

Description

NH-Sicherungseinsatz mit Messerkontakt nach IEC 60269-2, Baugröße NH000, gG, 500V AC, 100A, mit Kombi-Kennmelder, mit spannungsführender Grifflasche

Features

ETIM - Code:	EC000055
Rated voltage AC:	500 V
Rated breaking capacity AC:	120 kA
Type:	MooogL100
Class:	Ganzbereichssicherung, für allgemeine Anwendungen, hauptsächlich Kabel- und Leitungsschutz
Operating Joule integral 254V:	55,580 A²s
Operating Joule integral 440V:	99,700 A²s
Operating Joule integral 550V:	141,000 A²s
Pre-arcing Joule integral:	25000 A²s
Power dissipation at 70% rated current:	3.0 W
Size:	NH000
Rated current:	100 A
Product standard:	• IEC 60269-1 • IEC 60269-2 • DIN VDE 0636-2
Utilization category:	gG
Indicator / Signalling:	Combi indicator
Contact type:	Blade contact
Gripping lugs:	live
Power dissipation at rated current:	6.6 W
Packaging unit:	3

Further developments of our products and technical changes are subject to change. Alterations, errors and errata constitute no claim for damages. Our valid sales terms and delivery conditions are available on our website http://www.jeanmueller.de

Printed at: 28.07.2026 / 23:21

Documents

Catalogue NH-fuse-links gG

Catalogue Appendix

CE-conformity declaration

Datasheet	Peak let-through current chart		Download
Datasheet	Time current characteristics		Download
Datasheet	RoHS-Erklaerung_JM_DE.pdf		Download